

PATCHPANELS

EXCLUSIVE SERIES ODF BOXES

19" 4U 168 PORT TRAY TYPE

4U

19"

168
PORTW
TRAY

The TTAF Fiber Optic Termination Boxes are used to terminate and distribute optical fiber cables, termination box is ranging from 12 ports to 168 ports. They are convenient equipment to organize and connect the fiber optic links. It is suitable for the use in telecommunication network, central office optical

cable system and premise fiber network. Each fiber optic termination box is fully loaded with adaptors, splice trays and accessories and is ready for installation. TTAF supplies various kinds of sliding type fiber optic patch panels with different optical adapter interface.

FEATURES



- Up to 168 Fo connections
- Available to suit only adapter type
- You can apply ST/SC/FC/E2000/MU/MTRJ/LC
- Without rail
- Maintains fiber bending radius throughout for terminated optical fibers at 30mm
- Units can be custom design
- Compatible with screwed adapters and screwless type adapters
- Can be supplied with:
 - » Pigtail
 - » Special splice cassette
 - » Heat Shrink splice protectors



TECHNICAL SPECIFICATIONS

Size (w:19", h:3U)	(w): 430mm x (d): 310mm x (h): 175mm
Weight	Approx 6,45 kg
Fiber Capacity	0-168 port
Adaptor Type	ST, FC, SC, LC, E2000, MTRJ, MU
Color	Ral9005 Black, Ral7035
Mounting	19" / 21" Rack Type
Material	Mild Steel